

Plug-in hose



-40 – 80 °C

Reinforced, double-layer, self-clamping polyurethane hoses for industrial applications. These hoses have been designed especially for equipping robots and machine components, and are particularly suitable as a conduit for water, air and various gases.

- Free of substances that impair paint adhesion
- Silicone-free, UV-resistant, cold-flexible
- Resistant to oils, oxygen, ozone, acids and dilute alkalis
- Temperature range -40 to +80 °C



Type	Order no.	Material	Colour	Ø inside mm	Ø inside inch	max. operating pressure bar	min. burst pressure bar	PU pce.
Plug-in hose DN6	82929299	PUR	Black	6.4	1/4	24.0	95.0	50
Plug-in hose DN10	82929240	PUR	Black	9.5	3/8	20.0	81.0	50
Plug-in hose DN13	82929268	PUR	Black	12.5	1/2	20.0	81.0	50
Plug-in hose DN6	82929298	PUR	Green	6.4	1/4	24	95.0	50
Plug-in hose DN10	82929242	PUR	Green	9.5	3/8	20.0	81.0	50
Plug-in hose DN13	82929262	PUR	Green	12.5	1/2	20.0	81.0	50
Plug-in hose DN6	82929297	PUR	Red	6.4	1/4	24	95.0	50
Plug-in hose DN10	82929244	PUR	Red	9.5	3/8	20.0	81.0	50
Plug-in hose DN13	82929264	PUR	Red	12.5	1/2	20.0	81.0	50
Plug-in hose DN6	82929294	PUR	Blue	6.4	1/4	24	95.0	50
Plug-in hose DN10	82929246	PUR	Blue	9.5	3/8	20.0	81.0	50
Plug-in hose DN13	82929266	PUR	Blue	12.5	1/2	20.0	81.0	50
Plug-in hose DN10	82929248	PUR	Grey	9.5	3/8	20.0	81.0	50